


Ring for spotlight fittings

5905339278098



The Kanlux ELNIS L is a fixture which consists of two parts forming a whole. It is a combination of two separate elements: the body (the main part) and the casing (the spacer ring), forming a perfectly matched whole. The ELNIS L is a fixture with a 25-mm high casing. The Kanlux ELNIS L is characterised by modern design and very-high quality of workmanship.

GENERAL DATA:

Colour: anthracite
Necessity of using self-shielding lamps: yes
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Decorative ring without a ceramic frame: yes
The product is not suitable to be covered with a heat-insulating material: yes
Height [mm]: 44
Diameter [mm]: 98
Assembly hole [mm]: Ø70


TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC
Maximum power [W]: max 10
Class of protection against electric shock: II/III
Light source: MR16/PAR16
Light source included: no
Cap: Gx5,3/GU10
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: aluminum alloy
Lighting-fixture angle regulation: none
IP class: 20

LOGISTIC DATA:

Packaging method: 50
Number of units in the secondary packaging: 1
Number of units in the packaging: 50
Net unit weight [g]: 160
Grammage [g]: 199.8
Length of a unit pack [cm]: 10
Width of a unit pack [cm]: 10
Height of a unit pack [cm]: 5
Weight of a cardboard box [kg]: 9.99
Width of a cardboard box [cm]: 21
Height of a cardboard box [cm]: 26.5

Ring for spotlight fittings



Length of a cardboard box [cm] : 52

Volume of a cardboard box [m³]: 0.028938

ADDITIONAL INFORMATION:

- Decorative ring without a ceramic frame

