

28002 BRAVO PU36W6060NW W

Flush-mounted LED panel without power supply included

5905339280022



Kanlux BRAVO panels are specially selected components for even greater satisfaction with their use. Aluminium framework, specially selected LED diodes, reflector and diffuser distracting light are just some of the assets of Kanlux BRAVO LED panels. High luminous efficacy is another asset of these panels. Kanlux BRAVO LED panels do not have any power supply included.

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

The product is not suitable to be covered with a heat-insulating material: yes

Feeder included: no

Driver [index]: 28025

Length [mm]: 595

Width [mm]: 595

Height [mm]: 11

Integrated LED light source: yes

Number of modules (LED light source): 2

TECHNICAL DATA:

Power-supply current [mA]: 800

Maximum power [W]: 36

Class of protection against electric shock: III

Lampshade material: plastic

Enclosure material: steel

Panel/frame material: aluminum alloy

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 4320

Luminous efficiency [lm/W]: 120

Useful luminous flux of the light source Φ_{use} [lm]: 3120

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000


Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80



28002 BRAVO PU36W6060NW W

Flush-mounted LED panel without power supply included



Service life [h]: 30000

Luminous-flux-retention factor at the end of rated service life :
L70B50

Number of on/off cycles: ≥ 15000

Lighting angle [°]: 110

Luminous efficiency of the lamp [lm/W]: 120

Ambient temperature range to which the product can be exposed: 5÷25

Connection type: przewód zakończony wtyczką - DC

Wire type: H03VVH2-F

Wire length [m]: 0.05

Wire diameter [mm²]: 0,5

Supply-cord type: direct current

Power-supply type: direct current

IP class: 20

Kształt: square

UGR: <19

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 6

Number of units in the secondary packaging : 1

Number of units in the packaging : 6

Net unit weight [g]: 2276

Grammage [g]: 2431.67

Length of a unit pack [cm]: 60.5

Width of a unit pack [cm]: 2.5

Height of a unit pack [cm]: 61

Weight of a cardboard box [kg]: 14.59002

Width of a cardboard box [cm]: 15

Height of a cardboard box [cm]: 64

Length of a cardboard box [cm]: 63


Volume of a cardboard box [m³]: 0.06048

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website
- The correct LED power supply available in the KANLUX range is required for proper operation
- LED panel without power supply included


28002 BRAVO PU36W6060NW W

Flush-mounted LED panel without power supply included



KANLUX S.A. (kat 28002) BRAVO PU36W6060NW W / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28002) BRAVO PU36W6060NW W
Lamps: 1 x BRAVO PU36W6060NW



ACCESSORIES

28502



CLIPS BRAVO S/P 60-62

Mounting support, used for building in BRAVO 6060/6262 fittings in a plasterboard suspended ceiling, 4 pcs. in a set (28502)

28503










CLIPS BRAVO S/P 12030

Mounting support, used for building in BRAVO 12030 fittings in a plasterboard suspended ceiling, 6 pcs. in a set (28503)




28002 BRAVO PU36W6060NW W

Flush-mounted LED panel without power supply included

	28505	SPN BRAVO S/P 12030	Universal steel rope for suspending lighting fittings 6 pcs. in a set (28505)
	28504	SPN BRAVO S/P 60-62	Universal steel rope for suspending lighting fittings 4 pcs. in a set (28504)
	28501	BRAVO S/P GRIP 12030	NT mounting holder 6 pcs. in a set (28501)
	27613	ADTR 6060 W	Surface mounting frame for panel 600x600 (27613)
	27610	ADTR 6060 SR	Surface mounting frame for panel 600x600 (27610)
	27615	ADTR 6060 B	Surface mounting frame for panel 600x600 (27615)
	27611	ADTR 12030 W	Surface mounting frame for panel 120x30 (27611)

28002 BRAVO PU36W6060NW W

Flush-mounted LED panel without power supply included

			
27612	ADTR 12030 SR	Surface mounting frame for panel 120x30 (27612)	
			
28025	BRAVO DRIVER 36W	LED power supply unit dedicated to BRAVO P / PU panels with power of 36W (28025)	
			
25591	PSR 100	Safety rope (25591)	
