


Recessed-mounted LED panel

5905339280220



Kanlux BRAVO S/SU panels are specially selected components for even greater satisfaction with their use. Aluminium framework, specially selected LED diodes, reflector and diffuser distracting light are just some of the assets of Kanlux BRAVO LED S/SU panels. High luminous efficacy (100lm/W) is another asset of these panels. Kanlux BRAVO LED panels do not have any power supply included.

GENERAL DATA:

Colour: white
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
The product is not suitable to be covered with a heat-insulating material: yes
Feeder included: no
Length [mm]: 1195
Width [mm]: 295
Height [mm]: 11
Integrated LED light source: yes

TECHNICAL DATA:

Power-supply current [mA]: 1050
Maximum power [W]: 40
Class of protection against electric shock: III
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 4000
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤6
Colour rendering index: 80
Service life [h]: 25000
Number of on/off cycles: ≥15000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 100
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: steel
Panel/frame material: aluminum alloy
Connection type: Cable terminated with a plug - DC
Wire type: H03VVH2-F
Wire length [m]: 0.05
Wire diameter [mm²]: 0,5
Power-supply type: direct current

28022 BRAVO S 40W12030NW W

Recessed-mounted LED panel




Lamp-heating time [s]: ≤ 1
Lamp-ignition time [s]: $\leq 0,5$
IP class: 20
DRIVER [index]: 28026

LOGISTIC DATA:

Packaging method: 6
Number of units in the secondary packaging: 1
Number of units in the packaging: 6
Net unit weight [g]: 2360
Grammage [g]: 2793.33
Length of a unit pack [cm]: 122
Width of a unit pack [cm]: 2.5
Height of a unit pack [cm]: 31.5
Weight of a cardboard box [kg]: 16.75998
Width of a cardboard box [cm]: 12
Height of a cardboard box [cm]: 35
Length of a cardboard box [cm]: 123
Volume of a cardboard box [m³]: 0.05166

ADDITIONAL INFORMATION:

- The correct LED power supply available in the KANLUX range is required for proper operation
- LED panel without power supply included




28022 BRAVO S 40W12030NW W

Recessed-mounted LED panel

KANLUX S.A. (kat 28022) BRAVO S 40W12030NW W / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28022) BRAVO S 40W12030NW W
Lamps: 1 x BRAVO S 40W12030NW



ACCESSORIES:

28502 CLIPS BRAVO S/P 60-62



Mounting support, used for building in BRAVO 6060/6262 fittings in a plasterboard suspended ceiling, 4 pcs. in a set (28502)

28503 CLIPS BRAVO S/P 12030



Mounting support, used for building in BRAVO 12030 fittings in a plasterboard suspended ceiling, 6 pcs. in a set (28503)

28500 BRAVO S/P GRIP 60-62



NT mounting holder 4 pcs. in a set (28500)

28501 BRAVO S/P GRIP 12030



NT mounting holder 6 pcs. in a set (28501)

28022 BRAVO S 40W12030NW W

Recessed-mounted LED panel

27613 ADTR 6060 W

Surface mounting frame for panel 600x600 (27613)



27610 ADTR 6060 SR

Surface mounting frame for panel 600x600 (27610)



27615 ADTR 6060 B

Surface mounting frame for panel 600x600 (27615)



27611 ADTR 12030 W

Surface mounting frame for panel 120x30 (27611)



27612 ADTR 12030 SR

Surface mounting frame for panel 120x30 (27612)



28026 BRAVO DRIVER 40W

LED power supply unit dedicated to BRAVO S / SU panels with power of 40W (28026)



Recessed-mounted LED panel

25591 PSR 100

Safety rope (25591)

