


LED power supply unit

5905339280251





Colour: white Place of application: Indoors Possibility of installation on a normally flammable surface: yes Compatible with a dimmer: no

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated current [A]: 0.2 Rated frequency [Hz]: 50 λ: 0,95 Maximum power [W]: 36 Class of protection against electric shock: || Material: plastic Connection type: Terminal block **Range of sections of wires used [mm²]**: 0,75÷1 Supply-cord type: direct current **Overload protection:** yes Overvoltage protection: yes Thermal protection: 110°C Short-circuit protection: yes Maximum temperature Ta [°C]: 25 Input voltage - PRI [V]: 220-240 Output voltage - SEC [V]: 30-42 Output current - sec [ma]: 800 **IP class**: 20 Tc [°C]: 75

LOGISTIC DATA:

Packaging method: 6 Number of units in the secondary packaging: 6 Number of units in the packaging: 60 Net unit weight [g]: 108 Grammage [g]: 137.17 Length of a unit pack [cm]: 15 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 3.5 Weight of a cardboard box [kg]: 8.2302 Width of a cardboard box [cm]: 34 Height of a cardboard box [cm]: 20 Length of a cardboard box [cm]: 42 Volume of a cardboard box [m³]: 0.02856



LED power supply unit

