

28029 BRAVO DRIVER 28W

LED power supply unit

5905339280299



GENERAL DATA:

Colour: white

Place of application: Indoors

Possibility of installation on a normally flammable surface: yes

Compatible with a dimmer: no

Length [mm]: 143

Width [mm]: 43

Height [mm]: 30

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated current [A]: 0,16

Rated frequency [Hz]: 50

λ : 0,95

Maximum power [W]: 28

Class of protection against electric shock: II

Material: plastic

Connection type: Terminal block

Range of sections of wires used [mm²]: 0,75÷1

Supply-cord type: direct current

Overload protection: yes

Overvoltage protection: yes

Thermal protection: 110°C

Short-circuit protection: yes

Maximum temperature Ta [°C]: 25

Input voltage - PRI [V]: 220-240

Output voltage - SEC [V]: 30-42

Output current - sec [ma]: 750

IP class: 20

Tc [°C]: 75

LOGISTIC DATA:

Packaging method: 6

Number of units in the secondary packaging: 6

Number of units in the packaging: 60

Net unit weight [g]: 104

Grammage [g]: 135

Length of a unit pack [cm]: 15

Width of a unit pack [cm]: 5.5

Height of a unit pack [cm]: 3.5

Weight of a cardboard box [kg]: 8.1

Width of a cardboard box [cm]: 35.5

Height of a cardboard box [cm]: 20.5

Length of a cardboard box [cm]: 41

Volume of a cardboard box [m³]: 0.029838



