

28341 KDB-F54P-M

KDB-series distribution board

5905339283412



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

GENERAL DATA:

Colour: white

Door colour: white

Place of assembly: Recessed mount in the wall

Norm: PN-EN 62208

Length [mm]: 435

Width [mm]: 145

Height [mm]: 605

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 63

Rated frequency [Hz]: 50

Class of protection against electric shock: II

Material: plastic

Number of modules: 18P

Temperature resistance [°C]: 650

IK class: 07

IP class: 30

number of rows: 1

Ilość zacisków N/PE: 11+11

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the packaging: 1

Net unit weight [g]: 4450

Grammage [g]: 5930

Length of a unit pack [cm]: 63

Width of a unit pack [cm]: 47

Height of a unit pack [cm]: 18.5


Weight of a cardboard box [kg]: 5.93

Width of a cardboard box [cm]: 47

Height of a cardboard box [cm]: 18.5

28341 KDB-F54P-M

KDB-series distribution board



Length of a cardboard box [cm] : 63

Volume of a cardboard box [m³] : 0.054779