

## **28453** AL 4LED 150-MPR-B-NT

## T8 LED tube linear fittings


## 5905339284532













### **GENERAL DATA:**

Colour: black

Place of assembly: ceiling mounted Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Fixture lighting direction: down

Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1540 Width [mm]: 60 Height [mm]: 69

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 58

Class of protection against electric shock: |

Lampshade material: plastic

**Light source**: T8 LED **Light source included**: no

**Cap**: G13

Ambient temperature range to which the product can be

exposed: 5÷25

Shade type: microprismatic

**Enclosure material**: aluminum alloy **Connection type**: Self-clamping block

Range of sections of wires used [mm $^2$ ]: 1,5 $\div$ 2,5

IP class: 20

## LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1860 Grammage [g]: 2300

Length of a unit pack [cm]: 182 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 2.3 Width of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 7 Length of a cardboard box [cm]: 182 Volume of a cardboard box [m³]: 0.014014






# 28453 AL 4LED 150-MPR-B-NT

# T8 LED tube linear fittings


#### KANLUX S.A. (kat 28453) AL 4LED 150-MPR-B-NT + GLASSv4 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28453) AL 4LED 150-MPR-B-NT + GLASSv4 Lamps: 1 x T8 LED GLASSv4 24W-NW



#### KANLUX S.A. (kat 28453) AL 4LED 150-MPR-B-NT + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28453) AL 4LED 150-MPR-B-NT + GLASSV3 Lamps: 1 x T8 LED GLASSV3 24W-NW







# 28453 AL 4LED 150-MPR-B-NT

# T8 LED tube linear fittings

