Kanlux 28783 MINI BORD DLP-50-B


Ring for spotlight fittings 5905339287830













The Mini version of the BORD fixtures. A perfect alternative for people who want to use surface-mounted fixtures in a suspended ceiling, because the manner of installation is the same as for recessed-eyelet fixtures. An additional advantage is the angular adjustment of the MINI BORD fixtures within the range of 30°.

GENERAL DATA:

Colour: black Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Decorative ring without a ceramic frame: yes The product is not suitable to be covered with a heatinsulating material: yes Height [mm]: 50 Diameter [mm]: 98 Assembly hole [mm]: Ø85

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC Maximum power [W]: max 10 Class of protection against electric shock: II/III Light source: MR16/PAR16 Light source included: no Cap: Gx5,3/GU10 Ambient temperature range to which the product can be exposed: 5÷25 Enclosure material: aluminum alloy, steel Lighting-fixture angle regulation: in one axis Lighting-fixture angle regulation [°]: 30 IP class: 20


LOGISTIC DATA:

Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Number of units per layer on a pallet: 300 Net unit weight [g]: 200 Grammage [g]: 244 Length of a unit pack [cm]: 10 Width of a unit pack [cm]: 10 Height of a unit pack [cm]: 5.5 Weight of a cardboard box [kg]: 12.2





Ring for spotlight fittings



Width of a cardboard box [cm]: 22 Height of a cardboard box [cm]: 30 Length of a cardboard box [cm] : 54 Volume of a cardboard box [m³]: 0.03564

ADDITIONAL INFORMATION:

• Decorative ring without a ceramic frame