

Downlight fitting

5905339289377

IP
44/20

EA
SY
Installation



Kanlux ROUNDA V2LED is a new version of popular round downlight luminaires for indoor use. The downlights combine aesthetic design with light obtained thanks to LED technology. No water or dust can get to the inside owing to the high class of tightness (IP44).

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Height [mm]: 20

Diameter [mm]: 120

Assembly hole [mm]: Ø106

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 6

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 330

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80

Service life [h]: 15000

Number of on/off cycles: ≥ 20000

Lighting angle [°]: 110

Luminous efficiency of the lamp [lm/W]: 55

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Free cable ends

Wire length [m]: 0.05


Wire diameter [mm²]: 0.75

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

28937 ROUNDA V2LED6W-NW-W

Downlight fitting



IP class: 44/20

LOGISTIC DATA:

Packaging method: 40

Number of units in the secondary packaging: 1

Number of units in the packaging: 40

Net unit weight [g]: 140

Grammage [g]: 204.5

Length of a unit pack [cm]: 13

Width of a unit pack [cm]: 3

Height of a unit pack [cm]: 19


Weight of a cardboard box [kg]: 8.18

Width of a cardboard box [cm]: 33

Height of a cardboard box [cm]: 29

Length of a cardboard box [cm]: 40

Volume of a cardboard box [m³]: 0.03828



KANLUX S.A. (kat 28937) ROUNDA V2LED6W-NW-W / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28937) ROUNDA V2LED6W-NW-W
Lamps: 1 x ROUNDA V2LED6W-NW-W

