


# 28979 ONTEC G E1E180MATW

Emergency lighting LED 5902052563340







Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

#### GENERAL DATA:

Colour: white Place of assembly: ceiling mounted Place of application: Indoors Length [mm]: 250 Width [mm]: 29 Height [mm]: 194 Integrated LED light source: yes

#### **TECHNICAL DATA:**

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Rated power [W]: 3 Rated power (LED) [W]: 0.9 Class of protection against electric shock : II Lampshade material: plastic Diode type: LED SMD Colour temperature: cold white Correlated colour temperature [K]: 5000 Ambient temperature range to which the product can be exposed: 10+35 Battery (type): LiFePO4/C Battery (parameters): 3,2V 1,5Ah Operating mode: emergency and network Application: marking of escape routes Fail-safe working time [h]: 3 Automatic test: yes Enclosure material: plastic Connection type: Self-clamping block IP class: 20

#### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1 Number of units in the secondary packaging: 1 Number of units in the packaging: 1 Net unit weight [g]: 402

Date of issue: 18.12.2024, 13:01 We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





## 28979 ONTEC G E1E180MATW

### Emergency lighting LED

Grammage [g]: 464 Gross unit weight [g]: 464 Length of a unit pack [cm]: 26 Width of a unit pack [cm]: 4 Height of a unit pack [cm]: 14.5 Weight of a cardboard box [kg]: 0.464 Width of a cardboard box [cm]: 4 Height of a cardboard box [cm]: 14.5 Length of a cardboard box [cm]: 26 Volume of a cardboard box [m<sup>3</sup>]: 0.001508

#### ACCESSORIES

33813

ZESt MONT OG00 W



