


28979 ONTEC G E1E180MATW

Emergency lighting LED

5902052563340

















Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

GENERAL DATA:

Colour: white

Place of assembly: ceiling mounted Place of application: Indoors

Length [mm]: 250 Width [mm]: 29 Height [mm]: 194

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Rated power [W]: 3

Rated power (LED) [W]: 0.9

Class of protection against electric shock: ||

Lampshade material: plastic

Diode type: LED SMD

Colour temperature: cold white

Correlated colour temperature [K]: 5000

Ambient temperature range to which the product can be

exposed: 10÷35

Battery (type): LiFePO4/C

Battery (parameters): 3,2V 1,5Ah

Operating mode: emergency and network **Application**: marking of escape routes

Fail-safe working time [h]: 3

Automatic test: yes

Enclosure material: plastic

Connection type: Self-clamping block

IP class: 20

LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Date of issue: 16.11.2022, 21:35

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.






28979 ONTEC G E1E180MATW

Emergency lighting LED



33813 ZESt MONT OG00 W





We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

