

29071 PORTOS LED SE

Ceiling-mounted LED light fitting

5905339290717

IP
54

LED
technology



Kanlux PORTOS LED is a facade luminaire. Thanks to it, you can illuminate the facade and highlight the property number. Kanlux PORTOS LED in its universal form perfectly fits any surface. Perfectly smooth walls add character, and on facades such as brick, cladding board or structural plaster, it emphasizes the shape and brings out their uniqueness. Kanlux PORTOS LED is a durable and resistant to external factors luminaire that can be used both indoors and outdoors, without fear that moisture and dust will reduce its work efficiency. The Kanlux PORTOS LED SE version of the luminaire has a built-in dusk sensor and fixtures turns on automatically after dark.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Length [mm]: 262

Width [mm]: 166

Height [mm]: 51

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 5

Class of protection against electric shock: II

Lampshade material: PC

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 450

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80

Service life [h]: 30000

Number of on/off cycles: ≥15000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 90

Ambient temperature range to which the product can be exposed: -10÷35


Enclosure material: PC

Sensor type: dusk

Connection type: Self-clamping block

29071 PORTOS LED SE

Ceiling-mounted LED light fitting



Range of sections of wires used [mm²]: 0,5÷1,5

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 54

The luminaire starts automatically after dark: <20lx
(+/-10lx)

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 20

Number of units in the secondary packaging: 1

Number of units in the packaging: 20

Net unit weight [g]: 470

Grammage [g]: 590

Length of a unit pack [cm]: 17

Width of a unit pack [cm]: 6

Height of a unit pack [cm]: 27

Weight of a cardboard box [kg]: 11.8

Width of a cardboard box [cm]: 29

Height of a cardboard box [cm]: 37

Length of a cardboard box [cm]: 63

Volume of a cardboard box [m³]: 0.067599

ADDITIONAL INFORMATION:

- Fixtures turns on automatically after dark.

