

## **29113** MILENO EL-30 ASR-AN

Wall & ceiling lighting fitting


5905339291134













Kanlux MILENO follows the latest trends. The advantages of this series are its interesting desig and original shape. The very-large number of Kanlux MILENO fixture models means manymore arrangement possibilities.

#### **GENERAL DATA:**

Colour: silver / copper

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Height [mm]: 120 Diameter [mm]: 200

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Maximum power [W]: 3 x max 10

Class of protection against electric shock: |

**Light source**: PAR16 **Light source included**: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: steel

Connection type: Bolt terminal block

Range of sections of wires used [mm<sup>2</sup>]:  $1 \div 2,5$ The fixture is movable horizontally [°]: 300The fixture is movable vertically [°]: 80

IP class: 20

## **LOGISTIC DATA:**

Packaging method: 12

Number of units in the secondary packaging: 1


Number of units in the packaging: 12

Net unit weight [g]: 660 Grammage [g]: 923.33

Length of a unit pack [cm]: 24 Width of a unit pack [cm]: 13 Height of a unit pack [cm]: 24

Weight of a cardboard box [kg]: 11.07996

Width of a cardboard box [cm]: 41
Height of a cardboard box [cm]: 50
Length of a cardboard box [cm]: 49
Volume of a cardboard box [m³]: 0.10045





Photometry: the results obtained from testing were from a specific sample.





# **29113** MILENO EL-30 ASR-AN

# Wall & ceiling lighting fitting





Date of issue: 15.11.2022, 08:14

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.