

29117 MILENO EL-3I ASR-AN

Wall & ceiling lighting fitting


5905339291172













Kanlux MILENO follows the latest trends. The advantages of this series are its interesting desig and original shape. The very-large number of Kanlux MILENO fixture models means manymore arrangement possibilities.

GENERAL DATA:

Colour: silver / copper

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Length [mm]: 485 Width [mm]: 105 Height [mm]: 140

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Maximum power [W]: 3 x max 10

Class of protection against electric shock: |

Light source: PAR16 Light source included: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: steel

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: $1 \div 2,5$ The fixture is movable horizontally [°]: 300The fixture is movable vertically [°]: 80

IP class: 20

LOGISTIC DATA:

Packaging method: 8

Number of units in the secondary packaging: 1

Number of units in the packaging: 8

Net unit weight [g]: 610 Grammage [g]: 870

Length of a unit pack [cm]: 15.5 Width of a unit pack [cm]: 9.5 Height of a unit pack [cm]: 55

Weight of a cardboard box [kg]: 6.96
Width of a cardboard box [cm]: 32
Height of a cardboard box [cm]: 41
Length of a cardboard box [cm]: 56
Volume of a cardboard box [m³]: 0.073472

Date of issue: 15.11.2022, 08:13

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





29117 MILENO EL-3I ASR-AN

Wall & ceiling lighting fitting

