

29119 MILENO EL-41 ASR-AN

Wall & ceiling lighting fitting


5905339291196













Kanlux MILENO follows the latest trends. The advantages of this series are its interesting desig and original shape. The very-large number of Kanlux MILENO fixture models means manymore arrangement possibilities.

GENERAL DATA:

Colour: silver / copper

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Length [mm]: 715 Width [mm]: 105 Height [mm]: 140

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Maximum power [W]: 4 x max 10

Class of protection against electric shock: |

Light source: PAR16 **Light source included**: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: steel

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: $1 \div 2,5$ The fixture is movable horizontally [°]: 300The fixture is movable vertically [°]: 80

IP class: 20

LOGISTIC DATA:

Packaging method: 6

Number of units in the secondary packaging: 1

Number of units in the packaging: 6

Net unit weight [g]: 820 Grammage [g]: 1110

Length of a unit pack [cm]: 16 Width of a unit pack [cm]: 13 Height of a unit pack [cm]: 41.5

Weight of a cardboard box [kg]: 6.66
Width of a cardboard box [cm]: 34
Height of a cardboard box [cm]: 42
Length of a cardboard box [cm]: 42.5
Volume of a cardboard box [m³]: 0.06069

Date of issue: 15.11.2022, 08:16

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





29119 MILENO EL-4I ASR-AN

Wall & ceiling lighting fitting



Date of issue: 15.11.2022, 08:16 We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.