

Wall & ceiling lighting fitting

5905339291226



MO
DE
RN
design



Kanlux LAURIN spotlights provide a very large selection of directional ceiling and wall lamps. The simple and minimalist design can be successfully used in many rooms in the house. Free adjustment of the luminous flux direction is an additional advantage of these fixtures.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Length [mm]: 220

Width [mm]: 70

Height [mm]: 108

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 2 x max 35

Class of protection against electric shock: I

Light source: PAR16

Light source included: no

Cap: GU10

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

The fixture is movable horizontally [°]: 310

The fixture is movable vertically [°]: 90

IP class: 20

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 510

Grammage [g]: 601

Length of a unit pack [cm]: 11.5

Width of a unit pack [cm]: 7.5

Height of a unit pack [cm]: 22.5

Weight of a cardboard box [kg]: 6.01

Width of a cardboard box [cm]: 24.5

Height of a cardboard box [cm]: 25

Length of a cardboard box [cm]: 39.5

Wall & ceiling lighting fitting

Volume of a cardboard box [m³]: 0.024194