

29124 LAURIN EL-31 W

Wall & ceiling lighting fitting


5905339291240













Kanlux LAURIN spotlights provide a very large selection of directional ceiling and wall lamps. The simple and minimalist design can be successfully used in many rooms in the house. Free adjustment of the luminous flux direction is an additional advantage of these fixtures.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Length [mm]: 335 Width [mm]: 70 Height [mm]: 108

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Maximum power [W]: 3 x max 35

Class of protection against electric shock: I

Light source: PAR16 Light source included: no

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: aluminum alloy **Connection type**: Bolt terminal block

Range of sections of wires used [mm 2]: 1÷2,5 The fixture is movable horizontally [$^\circ$]: 310 The fixture is movable vertically [$^\circ$]: 90

IP class: 20

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 1


Number of units in the packaging: 10

Net unit weight [g]: 810 Grammage [g]: 934

Length of a unit pack [cm]: 11.5 Width of a unit pack [cm]: 7.5 Height of a unit pack [cm]: 35.5 Weight of a cardboard box [kg]: 9.34 Width of a cardboard box [cm]: 24

Height of a cardboard box [cm]: 37.5 Length of a cardboard box [cm]: 39.5









29124 LAURIN EL-3I W

Wall & ceiling lighting fitting



Volume of a cardboard box [m³]: 0.03555

