

29162 ORTE LED 18W-NW-O-SE

Ceiling-mounted LED light fitting

5905339291622















Kanlux ORTE LED is a new family of wall and ceiling fixtures in which particular attention has been paid to design and ease of installation. For added convenience, you can also choose from various motion detector versions.

GENERAL DATA:

Colour: white

Place of assembly: ceiling mounted, wall mounted

Place of application: Indoors and outdoors
Micro-interval between relay contacts: yes

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Wykrywanie ruchu: yes

Height [mm]: 65
Diameter [mm]: 250
Sensitivity regulation: yes

Mercury content: no

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 18

Class of protection against electric shock: ||

Lampshade material: plastic

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 1600

Useful luminous flux of the light source Φ use [lm]: 2200 Useful luminous flux of the light source Φ use [lm]: in

sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 20000

Luminous-flux-retention factor at the end of rated

service life: L70B50

Number of on/off cycles: ≥20000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 89

Ambient temperature range to which the product can be

exposed: -20÷35

Enclosure material: plastic **Sensor type**: microwave

Connection type: Self-clamping block

Date of issue: 16.11.2022, 04:41


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





29162 ORTE LED 18W-NW-O-SE

Ceiling-mounted LED light fitting





Range of sections of wires used [mm²]: 0,75÷2,5 Sensor-operation time [second-minute]: 5-5

Lamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5 sensor working angle [°]: 360

Illumination-level setpoint by which the sensor detects

movement [lx]: 2/10/50/off

IP class: 54

Sensor range[m]: max 6

LOGISTIC DATA:


Packaging method: 10

Number of units in the secondary packaging: ${\bf 1}$

Number of units in the packaging: 10

Net unit weight [g]: 480 Grammage [g]: 681

Length of a unit pack [cm]: 25.5
Width of a unit pack [cm]: 7
Height of a unit pack [cm]: 25.5
Weight of a cardboard box [kg]: 6.81
Width of a cardboard box [cm]: 37.5
Height of a cardboard box [cm]: 28.5
Length of a cardboard box [cm]: 52
Volume of a cardboard box [m³]: 0.055575





29162 ORTE LED 18W-NW-O-SE

Ceiling-mounted LED light fitting

