


31111 HIBO LED N 50W-NW

High-bay LED light fitting 8595665311117

















HIBO LED is a "High Bay" luminaire using a LED module with SMD diodes. The luminaire has a high rating of tightness IP65, thanks to which it can be mounted in places of high dustiness and exposed to water. It is an industrial luminaire suitable for lighting of storehouses, production halls and large commercial spaces.

GENERAL DATA:

Colour: black

Place of assembly: ceiling mounted

Place of application: for industrial applications

Minimum distance from the illuminated object: 1m

Compatible with a dimmer: no Fixture lighting direction: down

Height [mm]: 124 Diameter [mm]: 240 Mercury content: no

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 50

Class of protection against electric shock: I

Diode type: LED SMD **Luminous flux [lm]**: 4750

Useful luminous flux of the light source Φ use [lm] : 4000 Useful luminous flux of the light source Φ use [lm] : w szerokim

stożku (120°)

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 25000

Number of on/off cycles: ≥20000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 95

Ambient temperature range to which the product can be

exposed: -20÷40

Enclosure material: aluminum alloy Protective glass material: glass Connection type: Free cable ends

Wire type: H05RN-F Wire length [m]: 0.45

Date of issue: 16.01.2024, 23:42

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





31111 HIBO LED N 50W-NW

High-bay LED light fitting



Wire diameter [mm²]: 1 Lamp-heating time [s]: ≤1 Lamp-ignition time [s]: ≤0,5

IP class: 65

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1


Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1270 Grammage [g]: 1440


Gross unit weight [g]: 1476 Length of a unit pack [cm]: 25 Width of a unit pack [cm]: 26 Height of a unit pack [cm]: 10

Weight of a cardboard box [kg]: 1.44
Width of a cardboard box [cm]: 26
Height of a cardboard box [cm]: 10
Length of a cardboard box [cm]: 25
Volume of a cardboard box [m³]: 0.0065



MILEDO (kat 31111) HIBO LED N 50W-NW / LDC (Polar)





Date of issue: 16.01.2024, 23:42

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





31111 HIBO LED N 50W-NW

High-bay LED light fitting

Date of issue: 16.01.2024, 23:42

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

