


31173 BAREV BL LEDN2 40W-NW

LED panel

8595665311735



GENERAL DATA:

Colour: white
Place of assembly: ceiling mounted, Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object : 0,5m
Compatible with a dimmer: no
The product is not suitable to be covered with a heat-insulating material: yes
Length [mm]: 595
Width [mm]: 595
Height [mm]: 28
Integrated LED light source : yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 40
Class of protection against electric shock : I
Lampshade material: plastic
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 4000
Useful luminous flux of the light source Φ_{use} [lm] : 5000
Useful luminous flux of the light source Φ_{use} [lm] : in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses : ≤ 6
Colour rendering index: 80
Service life [h]: 30000
Number of on/off cycles: ≥ 15000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 100
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: steel
Connection type: Terminal block
Lamp-heating time [s]: ≤ 1
Lamp-ignition time [s]: $\leq 0,5$
IP class: 20

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 6
Number of units in the secondary packaging : 1

31173 BAREV BL LEDN2 40W-NW

LED panel

Number of units in the packaging: 6**Net unit weight [g]:** 1956**Grammage [g]:** 2003.33**Length of a unit pack [cm]:** 60.5**Width of a unit pack [cm]:** 61**Height of a unit pack [cm]:** 3**Weight of a cardboard box [kg]:** 12.01998**Width of a cardboard box [cm]:** 22**Height of a cardboard box [cm]:** 63**Length of a cardboard box [cm]:** 61**Volume of a cardboard box [m³]:** 0.084546