

31495 TOLU C LED 6W-NW-W


Bulkhead fixture 8595665314958













Colour: white

Place of assembly: wall mounted, ceiling mounted Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,5m Compatible with a dimmer: no Mercury content: no Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 6 Class of protection against electric shock : II Lampshade material: plastic Diode type: LED SMD Luminous flux of the light fitting [lm]: 420 Colour temperature: white Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: 6 Colour rendering index: 80 Service life [h]: 20000 Number of on/off cycles: ≥15000 Lighting angle [°]: 120 Luminous efficiency of the lamp [lm/W]: 70 Ambient temperature range to which the product can be exposed: -20+40 Enclosure material: plastic Connection type: Self-clamping block Range of sections of wires used [mm²]: 0,5-2,5 **IP class**: 54

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 100 Number of units in the secondary packaging: 1 Number of units in the packaging: 100 Net unit weight [g]: 80 Grammage [g]: 98.8 Gross unit weight [g]: 90 Length of a unit pack [cm]: 16 Width of a unit pack [cm]: 8.5 Height of a unit pack [cm]: 4

Date of issue: 18.01.2024, 13:05

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





31495 TOLU C LED 6W-NW-W

Bulkhead fixture

Weight of a cardboard box [kg]: 9.88 Width of a cardboard box [cm]: 41 Height of a cardboard box [cm]: 34.5 Length of a cardboard box [cm] : 43.5 Volume of a cardboard box [m³]: 0.061531

