

Kanlux



EAN: 5905339325198

LED wall mounted fitting
Kanlux 32519 TONIL II LED B/G


FLEXIBLE
arm



Date of issue: 03.02.2026, 14:36

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN

PRODUCT PARAMETERS

Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Maximum power [W]	3,3
Luminous flux [lm]	145
Luminous efficiency of the lamp [lm/W]	44
Lighting angle [°]	30
Diode type	LED SMD
Integrated LED light source	yes
Correlated colour temperature [K]	3000
Colour consistency in McAdam ellipses	≤6
Colour temperature	warm white
Colour rendering index	80
Service life [h]	20000
Number of on/off cycles	≥15000
Place of application	Indoors
IP class	20
Compatible with a dimmer	no
On switch	yes
The fixture is movable horizontally [°]	360
The fixture is movable vertically [°]	360
Control gear replaceability	Any control panel or control equipment can only be replaced by qualified personnel (Kanlux service only)
Product category according to 2019/2020/EU	Containing product (CP)
Mercury content	no
Mercury content in the lamp [mg]	0

DIMENSIONS AND MOUNTING

Height [mm]	120
Width [mm]	50
Length [mm]	370
Place of assembly	wall mounted
Connection type	Bolt terminal block
Range of sections of wires used [mm ²]	0,5-1,5

MATERIAL AND CONSTRUCTION

Colour	black/gold
Enclosure material	aluminum alloy
Lampshade material	plastic
Class of protection against electric shock	II
Minimum distance from the illuminated object	0,2m
Ambient temperature range to which the product can be exposed	5÷25

LIGHT SOURCE PARAMETERS

LED module	2ES103WW32000001
On-mode power of the light source P _{on} [W]	2,7
Energy consumption in on-mode of the light source (kWh/1000h)	3
Energy efficiency class of the light source in the contains product (CP)	G
Useful luminous flux of the light source Φ _{use} [lm]	145

LOGISTICS

Unit of measurement	unit
Packaging method	50
Number of units in the secondary packaging	1
Number of units in the packaging	50
Net unit weight [g]	320
Grammage [g]	402
Gross unit weight [g]	374
Length of a unit pack [cm]	12.5
Width of a unit pack [cm]	5.5
Height of a unit pack [cm]	19
Weight of a cardboard box [kg]	20.1

Date of issue: 03.02.2026, 14:36

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

LIGHT SOURCE PARAMETERS	
Useful luminous flux of the light source Φ_{use} [lm]	in narrow cone (90°)
Height of the light source [mm]	23
Width of the light source [mm]	23
Depth of the light source [mm]	8
Chromaticity coordinates (x)	0,44
Chromaticity coordinates (y)	0,403
R9 colour rendering index value	-5
Survival factor	0,9
The lumen maintenance factor	0,95
Peak luminous intensity [cd]	365
Beam angle [°]	30
Colour-tuneable light source	no
High luminance light source	no
Anti-glare shield	no
Dimmable	no
LED light source replaceability	It is not possible to replace the LED light source

LOGISTICS	
Width of a cardboard box [cm]	31.5
Height of a cardboard box [cm]	40.5
Length of a cardboard box [cm]	65
Volume of a cardboard box [m ³]	0.082924

ADDITIONAL INFORMATION
3 years Warranty under the terms of the warranty statement, available on our website