


32523 TONIL II LED W

LED wall mounted fitting

5905339325235



Kanlux TONIL LED II is a modest in form model with an integrated light source. Its flexible, rubber arm allows you to direct the lighting in the desired direction. At the same time, we can give it the desired shape.

GENERAL DATA:

Colour: white
Place of assembly: wall mounted
Place of application: Indoors
Minimum distance from the illuminated object: 0,2m
Compatible with a dimmer: no
On switch: yes
Length [mm]: 370
Width [mm]: 51
Height [mm]: 121
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 3,3
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 145
Useful luminous flux of the light source Φ_{use} [lm]: 145
Useful luminous flux of the light source Φ_{use} [lm]: in narrow cone (90°)
Colour temperature: Warm white
Correlated colour temperature [K]: 3000
Colour consistency in McAdam ellipses: ≤ 6
Colour rendering index: 80
Service life [h]: 20000
Number of on/off cycles: ≥ 15000
Lighting angle [°]: 30
Luminous efficiency of the lamp [lm/W]: 44
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: aluminum alloy
Connection type: Bolt terminal block
Range of sections of wires used [mm²]: 0,5-1,5
Lamp-heating time [s]: ≤ 1
Lamp-ignition time [s]: $\leq 0,5$
The fixture is movable horizontally [°]: 360

LED wall mounted fitting

The fixture is movable vertically [°]: 360
IP class: 20

LOGISTIC DATA:

Packaging method: 50
Number of units in the secondary packaging: 1
Number of units in the packaging: 50
Net unit weight [g]: 320
Grammage [g]: 402
Length of a unit pack [cm]: 12.5
Width of a unit pack [cm]: 5.5
Height of a unit pack [cm]: 19
Weight of a cardboard box [kg]: 20.1
Width of a cardboard box [cm]: 31.5
Height of a cardboard box [cm]: 40.5
Length of a cardboard box [cm]: 65
Volume of a cardboard box [m³]: 0.082924

