


## 32825 OS 40W-840-MPRM-B-N3

Surface-mounted LED office fixture

5905339328250



### GENERAL DATA:

**Colour:** black

**Place of assembly:** ceiling mounted

**Place of application:** Indoors

**Minimum distance from the illuminated object:** 0,5m

**Compatible with a dimmer:** no

**The product is not suitable to be covered with a heat-insulating material:** yes

**Length [mm]:** 1200

**Width [mm]:** 300

**Height [mm]:** 35

**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 40

**Class of protection against electric shock:** I

**Lampshade material:** plastic

**Diode type:** LED SMD

**Luminous flux [lm]:** 4300

**Colour temperature:** white

**Correlated colour temperature [K]:** 4000

**Colour consistency in McAdam ellipses:**  $\leq 3$

**Colour rendering index:** 80

**Service life [h]:** 50000

**Luminous-flux-retention factor at the end of rated service life:** L90B10

**Number of on/off cycles:**  $\geq 30000$

**Lighting angle [°]:** X90/Y95

**Luminous efficiency of the lamp [lm/W]:** 108

**Ambient temperature range to which the product can be exposed:** 5÷25

**Shade type:** m-type microprismatic

**Enclosure material:** Metal

**Connection type:** Self-clamping block

**Range of sections of wires used [mm<sup>2</sup>]:** 1,5÷2,5

**Lamp-heating time [s]:**  $\leq 1$

**Lamp-ignition time [s]:**  $\leq 0,5$

**IP class:** 20

### LOGISTIC DATA:

**Packaging method:** 1

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 1

**Net unit weight [g]:** 4190

Surface-mounted LED office fixture

**Grammage [g]:** 4620  
**Length of a unit pack [cm]:** 123  
**Width of a unit pack [cm]:** 32.5  
**Height of a unit pack [cm]:** 5.5  
**Weight of a cardboard box [kg]:** 4.62  
**Width of a cardboard box [cm]:** 32.5  
**Height of a cardboard box [cm]:** 5.5  
**Length of a cardboard box [cm] :** 123  
**Volume of a cardboard box [m<sup>3</sup>]:** 0.021986

### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 32825) OS 40W-840-MPRM-B-N3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 32825) OS 40W-840-MPRM-B-N3  
Lamps: 1 x OS 40W-840-MPRM-B-N3

