


32827 OS 40W-840-MPRM-B-P3

Recessed - Mounted LED Office Fixture

5905339328274



GENERAL DATA:

Colour: black

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Length [mm]: 1195

Width [mm]: 295

Height [mm]: 34

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 40

Class of protection against electric shock: I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 4400

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 3

Colour rendering index: 80

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥ 30000

Lighting angle [°]: X90/Y95

Luminous efficiency of the lamp [lm/W]: 110

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: m-type microprismatic

Enclosure material: Metal

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5÷2,5

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

IP class: 20

LOGISTIC DATA:

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 4030

Recessed - Mounted LED Office Fixture

Grammage [g]: 4490
Length of a unit pack [cm]: 123
Width of a unit pack [cm]: 33
Height of a unit pack [cm]: 6
Weight of a cardboard box [kg]: 4.49
Width of a cardboard box [cm]: 33
Height of a cardboard box [cm]: 6
Length of a cardboard box [cm] : 123
Volume of a cardboard box [m³]: 0.024354

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website