32828 OSD 40W-840-MPRM-W-P1

Recessed - Mounted LED Office Fixture

5905339328281



GENERAL DATA:

Colour: white
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: DALI
The product is not suitable to be covered with a heat-insulating material: yes
Length [mm]: 595
Width [mm]: 595
Height [mm]: 34
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 40
Class of protection against electric shock: I
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 4600
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤3
Colour rendering index: 80
Service life [h]: 50000
Luminous-flux-retention factor at the end of rated service life: L90B10
Number of on/off cycles: ≥30000
Lighting angle [°]: X95/Y95
Luminous efficiency of the lamp [lm/W]: 115
Ambient temperature range to which the product can be exposed: 5÷25
Shade type: m-type microprismatic
Enclosure material: Metal
Connection type: Self-clamping block
Range of sections of wires used [mm²]: 1,5÷2,5
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5
IP class: 20

LOGISTIC DATA:

Packaging method: 1
Number of units in the secondary packaging: 1
Number of units in the packaging: 1
Net unit weight [g]: 4100

We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN

32828 OSD 40W-840-MPRM-W-P1

Recessed - Mounted LED Office Fixture

Grammage [g]: 4460
Length of a unit pack [cm]: 63
Width of a unit pack [cm]: 61
Height of a unit pack [cm]: 5
Weight of a cardboard box [kg]: 4.46
Width of a cardboard box [cm]: 61
Height of a cardboard box [cm]: 5
Length of a cardboard box [cm] : 63
Volume of a cardboard box [m³]: 0.019215

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN