


32888 KRO10-2/B6/30

Residual-current circuit breaker with overcurrent module, 10kA, 2P

5905339328885



GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61009 -1

Length [mm]: 78

Width [mm]: 36

Height [mm]: 81

TECHNICAL DATA:

Rated voltage [V]: 230 AC

Rated current [A]: 6

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: 10÷16

Residual-current protection type: AC

Release characteristics: B

Energy-limit class: 3

Number of modules: 2

Differential-rated current [mA]: 30

Rated short-circuit current [A]: 10000

IP class: 20

Rated insulation voltage UI [V]: 400

Number of poles: 2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 6

Number of units in the secondary packaging: 6

Number of units in the packaging: 60

Net unit weight [g]: 196

Grammage [g]: 230

Gross unit weight [g]: 210

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 4

Height of a unit pack [cm]: 8

Weight of a cardboard box [kg]: 13.8

Width of a cardboard box [cm]: 27

32888 KRO10-2/B6/30

Residual-current circuit breaker with overcurrent module, 10kA, 2P

Height of a cardboard box [cm]: 19

Length of a cardboard box [cm] : 49.5

Volume of a cardboard box [m³]: 0.025394