

33121 FLINI IP44 DSL-W

Ring for spotlight fittings


5905339331212

















Kanlux FLINI are ceiling luminaires dedicated for bathrooms and rooms with increased humidity. Thanks to their design, they are resistant to moisture (IP44). Kanlux FLINI are available in two shapes - round and square. You can choose between matt white or matt black. Two such universal colours will allow us to match these lamps to almost any interior.

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Decorative ring without a ceramic frame: yes

The product is not suitable to be covered with a heat-

insulating material: yes

Length [mm]: 80 Width [mm]: 80 Height [mm]: 50

Assembly hole [mm]: Ø60

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC

Maximum power [W]: max 10

Class of protection against electric shock: ||/|||

Light source: MR16/PAR16 **Light source included**: no

Cap: Gx5,3/GU10

Enclosure material: aluminum alloy Lighting-fixture angle regulation: none

IP class: 44/20

LOGISTIC DATA:

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 110 Grammage [g]: 158

Length of a unit pack [cm]: 9
Width of a unit pack [cm]: 10
Height of a unit pack [cm]: 5.5
Weight of a cardboard box [kg]: 7.9
Width of a cardboard box [cm]: 23
Height of a cardboard box [cm]: 27.5

Length of a cardboard box [cm]: 47 Volume of a cardboard box [m³]: 0.029728




We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





33121 FLINI IP44 DSL-W

Ring for spotlight fittings



ADDITIONAL INFORMATION:

• Decorative ring without a ceramic frame

Date of issue: 15.11.2022, 05:03

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

