

TP STRONG LED 48W-NW 33170

Linear LED luminaire 5905339331700











Kanlux TP STRONG is a hermetic luminaire for special purposes. The tightness of IP65, mechanical resistance of IK08, and luminous efficacy of 135lm/W are the main advantages of this luminaire. Additionally, it has a light distribution angle of X125º/Y110º. The parameters speak for themselves, but we also give a 5-year warranty.

GENERAL DATA:


Colour: white

Place of assembly: ceiling mounted, wall mounted Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,5m Possibility of fixture-loop-through connection: yes Compatible with a dimmer: no Length [mm]: 1200 Width [mm]: 72 Height [mm]: 63 Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Power factor: 0.95 Maximum power [W]: 48 Class of protection against electric shock : | Lampshade material: PC Diode type: LED SMD Luminous flux [lm]: 6500 Useful luminous flux of the light source Quse [Im]: 8000 Useful luminous flux of the light source Quse [Im] : in sphere (360°) Colour temperature: white Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses : ≤6 Colour rendering index: 80 Service life [h]: 50000 Luminous-flux-retention factor at the end of rated service life : L70B50 Number of on/off cycles: ≥30000 Lighting angle [°]: X125/Y110 Luminous efficiency of the lamp [lm/W]: 135





Date of issue: 12.11.2024, 09:51



Kanlux

33170 TP STRONG LED 48W-NW

Linear LED luminaire




Ambient temperature range to which the product can be exposed: $-20 \div 40$ Enclosure material: plastic Connection type: Self-clamping block Range of sections of wires used [mm²]: $1,5 \div 2,5$ Lamp-heating time [s]: <1 Lamp-ignition time [s]: $\leq 0,5$ Maximum number of loop-through-connected fixtures: 15 IK class: 08 IP class: 65

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 6 Number of units in the secondary packaging: 1 Number of units in the packaging: 6 Net unit weight [g]: 1052 Grammage [g]: 1233.33 Length of a unit pack [cm]: 127.5 Width of a unit pack [cm]: 8 Height of a unit pack [cm]: 7 Weight of a cardboard box [kg]: 7.39998 Width of a cardboard box [cm]: 17 Height of a cardboard box [cm]: 17 Height of a cardboard box [cm]: 130 Volume of a cardboard box [m³]: 0.05083

ADDITIONAL INFORMATION:

• 5 years Warranty under the terms of the warranty statement, available on our website







33170 TP STRONG LED 48W-NW

Linear LED luminaire

KANLUX S.A. (kat 33170) TP STRONG LED 48W-NW / LDC (Polar)

Luminaire: KANLUX S.A. (kat 33170) TP STRONG LED 48W-NW Lamps: 1 x TP STRONG LED 48W

