

## **33174** BLINGO IPRN38W 6060NW

# Recessed-mounted LED panel 5905339331748
























Kanlux BLINGO LED IPRN are backlight panels characterized by increased tightness - IP44/20, which enables their use in places exposed to moisture. Kanlux BLINGO LED IPRN panel models have a non-integrated power supply included. These panels are flush-mounted, for surface-mounting use the appropriate Kanlux ADTR-H frame. The panels are equipped with a quick connector for easy installation.

#### **GENERAL DATA:**

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating

material: yes

Feeder included: yes Length [mm]: 595 Width [mm]: 595 Height [mm]: 25

Integrated LED light source: yes

#### **TECHNICAL DATA:**

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 38

Class of protection against electric shock: II

Lampshade material: PS Diode type: LED SMD

Luminous flux of the light fitting [lm]: 3800

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 50000

Number of on/off cycles: ≥50000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 100

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: iron
Panel/frame material: iron

Connection type: Self-clamping block

Date of issue: 11.07.2023, 13:41

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





# **33174** BLINGO IPRN38W 6060NW

## Recessed-mounted LED panel

Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IP class: 44/20

### **LOGISTIC DATA:**

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1550 Grammage [g]: 2038

Length of a unit pack [cm]: 60 Width of a unit pack [cm]: 3 Height of a unit pack [cm]: 61.5

Weight of a cardboard box [kg]: 10.19
Width of a cardboard box [cm]: 16.5
Height of a cardboard box [cm]: 63.5
Length of a cardboard box [cm]: 61.5
Volume of a cardboard box [m³]: 0.064437

