

#### **BLINGO TN24-28W6060NW** 33178

# Recessed-mounted LED panel 5905339331786



























Kanlux BLINGO LED TN24-28 are backlight panels with threestage power regulation (24W, 26W and 28W), which also determines the change of luminous flux. In Kanlux BLINGO LED TN24-28 panel models, there is no power supply included. These panels are flush-mounted, for surface-mounting use the appropriate Kanlux ADTR-H frame. The panels are equipped with a quick connector for easy installation.

### **GENERAL DATA:**

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating

material: yes

Feeder included: yes Length [mm]: 595 Width [mm]: 595 Height [mm]: 25

Integrated LED light source: yes

#### **TECHNICAL DATA:**

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 24/26/28

Class of protection against electric shock: ||

Lampshade material: PS Diode type: LED SMD

Luminous flux of the light fitting [lm]: 3400/3600/4000

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses : ≤6

Colour rendering index: 80 Service life [h]: 50000

Number of on/off cycles: ≥50000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 142/138

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: iron Panel/frame material: iron

Connection type: Self-clamping block

Date of issue: 11.07.2023, 15:50


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





# **33178** BLINGO TN24-28W6060NW

## Recessed-mounted LED panel





Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IP class: 20

### LOGISTIC DATA:

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1614 Grammage [g]: 2140

Length of a unit pack [cm]: 60 Width of a unit pack [cm]: 3 Height of a unit pack [cm]: 64

Weight of a cardboard box [kg]: 10.7 Width of a cardboard box [cm]: 16.5 Height of a cardboard box [cm]: 66 Length of a cardboard box [cm]: 62

Volume of a cardboard box [m³]: 0.067518

Date of issue: 11.07.2023, 15:50

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

