


ERINUS LED LL W-WW 33324

Staircase LED light fitting 5905339333247



















Kanlux ERINUS is a unique series of premium stairwaf fittings made of plastic. These luminaires are characterized by exceptional lightness due to the materials from which they were made, and at the same time they are made with great precision and attention to detail. Kanlux ERINUS are very thin, so they flush with the wall line and make it a discreet decoration. We have three colors to choose (white, black and gray), two colors of light (warm and neutral light) and three different models of luminaires. The Kanlux ERINUS L is a square luminaire glowing in one direction, the LL model shines in both directions, and the Kanlux ERINUS O is a round luminaire glowing in one direction.

GENERAL DATA:

To be built into the wall: yes

Colour: white

Place of assembly: Recessed mount in the wall

Place of application: Indoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no

Length [mm]: 75 Width [mm]: 16 Height [mm]: 75

Required diameter of the assembly box [Ømm]: 60

Assembly-hole dimensions [mm]: 60 Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 12 DC Maximum power [W]: 1.5

Class of protection against electric shock: |||

Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 30

Colour temperature: Warm white

Correlated colour temperature [K]: 3000 Colour consistency in McAdam ellipses : ≤6

Colour rendering index: 80 Service life [h]: 30000

Number of on/off cycles: ≥15000

Luminous efficiency of the lamp [lm/W]: 20

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: plastic


Date of issue: 05.07.2024, 16:16





33324 ERINUS LED LL W-WW

Staircase LED light fitting





Photometry: the results obtained from testing were from a specific sample.

Connection type: Free cable ends

Lamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 100

Number of units in the secondary packaging: 1

Number of units in the packaging: 100

Net unit weight [g]: 26
Grammage [g]: 48.9
Gross unit weight [g]: 41
Length of a unit pack [cm]: 11
Width of a unit pack [cm]: 2.5
Height of a unit pack [cm]: 16.5
Weight of a cardboard box [kg]: 4.89
Width of a cardboard box [cm]: 23
Height of a cardboard box [cm]: 35
Length of a cardboard box [cm]: 69.5
Volume of a cardboard box [m³]: 0.055948

0,8 0,6 0,4 0.2 180 400 440 480 520 560 600 640 680 720 760 800