


ERINUS LED LL B-WW 33336

Staircase LED light fitting 5905339333360













Kanlux ERINUS is a unique series of premium stairwaf fittings made of plastic. These luminaires are characterized by exceptional lightness due to the materials from which they were made, and at the same time they are made with great precision and attention to detail. Kanlux ERINUS are very thin, so they flush with the wall line and make it a discreet decoration. We have three colors to choose (white, black and gray), two colors of light (warm and neutral light) and three different models of luminaires. The Kanlux ERINUS L is a square luminaire glowing in one direction, the LL model shines in both directions, and the Kanlux ERINUS O is a round luminaire glowing in one direction.

GENERAL DATA:

To be built into the wall: yes Colour: black Place of assembly: Recessed mount in the wall Place of application: Indoors Minimum distance from the illuminated object: 0,1m Compatible with a dimmer: no Length [mm]: 75 Width [mm]: 16 Height [mm]: 75 Required diameter of the assembly box [Ømm]: 60 Assembly-hole dimensions [mm]: 60 Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 12 DC Maximum power [W]: 1.5 Class of protection against electric shock : III Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 30 Colour temperature: Warm white Correlated colour temperature [K]: 3000 Colour consistency in McAdam ellipses : ≤6 Colour rendering index: 80 Service life [h]: 30000 Number of on/off cycles: ≥15000 Luminous efficiency of the lamp [lm/W]: 20 Ambient temperature range to which the product can be exposed: 5+25 Enclosure material: plastic

Date of issue: 05.07.2024, 16:09


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





33336 ERINUS LED LL B-WW

Staircase LED light fitting





Connection type: Free cable ends Lamp-heating time [s]: ≤1 Lamp-ignition time [s]: ≤0,5 IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 100 Number of units in the secondary packaging: 1 Number of units in the packaging: 100 Net unit weight [g]: 26 Grammage [g]: 48.9 Gross unit weight [g]: 40 Length of a unit pack [cm]: 11 Width of a unit pack [cm]: 2.5 Height of a unit pack [cm]: 16.5 Weight of a cardboard box [kg]: 4.89 Width of a cardboard box [kg]: 4.89 Width of a cardboard box [cm]: 23 Height of a cardboard box [cm]: 35 Length of a cardboard box [cm]: 69.5 Volume of a cardboard box [m³]: 0.055948

