

## **33516** XLED A60 4W-SW

LED light source

5905339335166























A decorative version of a "true LED bulb". Kanlux XLED in this exceptional version will help you create a very cosy atmosphere. All thanks to a very warm colour of the light and an amber glass in which a spiral LED filament is enclosed. This bulb will become a decoration of your house, café, restaurant and any other place in which you will install it. It is an exceptional combination of a decorative nature, vintage style and modern energy-efficient LED technology.

### **GENERAL DATA:**

Colour: amber

Lamp designed for decorative lighting: Not applicable

Compatible with a dimmer: no

Height [mm]: 108
Diameter [mm]: 60
Mercury content: no

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Lamp-power factor: 0.5 Rated power [W]: 4

Lampshade material: glass

Light source: A60

Diode type: LED FILAMENT

Total rated luminous flux [lm]: 250

Useful luminous flux of the light source  $\Phi$ use [lm]: 250 Useful luminous flux of the light source  $\Phi$ use [lm]: in

sphere (360°)

Colour temperature: super warm

Correlated colour temperature [K]: 1800 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80

**Cap**: E27

Rated lamp-service life [h]: 15000 Number of on/off cycles: ≥20000 Rated beam angle [°]: 320 Lamp rated current [mA]: 38


Annual power consumption [kWh/1000h]: 4 Luminous efficiency of the lamp [lm/W]: 63

**Ignition time [s]**:  $\leq 0.5$ 

Lamp-heating time to 60% of the full luminous flux [s]:

Negligible

Lamp-heating time to 95% [s]: <2



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





# **33516** XLED A60 4W-SW

## LED light source

Lamp premature-failure indicator: <5% po 1000h Lamp service life factor after the period of 6000h [%]:  $\ge 90$ 

Luminous flux retention factor at the end of rated service life [%]:  $\geq 70$ 

Luminous flux retention factor after the period of 6000h

**[%]**: ≥80

Declaration of equality in power rating [W]: 25

Light source shape: standard

### LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 100

Net unit weight [g]: 34 Grammage [g]: 62.3

Length of a unit pack [cm]: 6.5
Width of a unit pack [cm]: 6.5
Height of a unit pack [cm]: 12
Weight of a cardboard box [kg]: 6.23
Width of a cardboard box [cm]: 35
Height of a cardboard box [cm]: 27
Length of a cardboard box [cm]: 69.5
Volume of a cardboard box [m³]: 0.065678

KANLUX S.A. (kat 33516) XLED A60 4W-SW / LDC (Polar)

