


## 33518 XLED G95 4W-SW

LED light source

5905339335180

**1800K**  
SUPER  
WARM



A decorative version of the GLOBE-type bulb. Kanlux XLED G95 will let you create a very cosy atmosphere. All thanks to a very warm colour of the light and an amber glass in which a spiral LED filament is enclosed. This ball of light will become a decoration of your house, café, restaurant and any other place in which you will install it. It is an exceptional combination of a decorative nature and a modern energy-efficient LED technology.

### GENERAL DATA:

**Colour:** amber

**Lamp designed for decorative lighting:** Not applicable

**Compatible with a dimmer:** no

**Height [mm]:** 140

**Diameter [mm]:** 95

**Mercury content:** no

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Lamp-power factor:** 0.5

**Rated power [W]:** 4

**Lampshade material:** glass

**Light source:** G95

**Diode type:** LED FILAMENT

**Total rated luminous flux [lm]:** 250

**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 250

**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)

**Colour temperature:** super warm

**Correlated colour temperature [K]:** 1800

**Colour consistency in McAdam ellipses:**  $\leq 6$

**Colour rendering index:** 80

**Cap:** E27

**Rated lamp-service life [h]:** 15000

**Number of on/off cycles:**  $\geq 20000$

**Rated beam angle [°]:** 320

**Lamp rated current [mA]:** 38

**Annual power consumption [kWh/1000h]:** 4

**Luminous efficiency of the lamp [lm/W]:** 63

**Ignition time [s]:**  $\leq 0,5$

**Lamp-heating time to 60% of the full luminous flux [s]:**  
Negligible

**Lamp-heating time to 95% [s]:**  $< 2$

**Lamp premature-failure indicator:** <5% po 1000h

**Lamp service life factor after the period of 6000h [%]:**  
≥90

**Luminous flux retention factor at the end of rated service life [%]:** ≥70

**Luminous flux retention factor after the period of 6000h [%]:** ≥80

**Declaration of equality in power rating [W]:** 25

**Light source shape:** globe

### LOGISTIC DATA:

**Packaging method:** 5

**Number of units in the secondary packaging:** 5

**Number of units in the packaging:** 40

**Net unit weight [g]:** 52

**Grammage [g]:** 135

**Length of a unit pack [cm]:** 10

**Width of a unit pack [cm]:** 10

**Height of a unit pack [cm]:** 16

**Weight of a cardboard box [kg]:** 5.4

**Width of a cardboard box [cm]:** 44

**Height of a cardboard box [cm]:** 35

**Length of a cardboard box [cm]:** 53

**Volume of a cardboard box [m<sup>3</sup>]:** 0.08162

KANLUX S.A. (kat 33518) XLED G95 4W-SW / LDC (Polar)

Luminaire: KANLUX S.A. (kat 33518) XLED G95 4W-SW  
Lamps: 1 x XLED G95 4W-SW

