




33613 LOGI 02-1230-142 cm

Socket Outlet Earthed - With Protection Cover - FireProof Plastic

5905339336132







A grounded single socket outlet (Schuko) allows you to power an electrical circuit with a maximum load of 16A. In addition, the socket outlet has a hinged lid, thanks to which it maintains the IP rating of IP 44 and may be installed in areas with splash water (bathrooms).

GENERAL DATA:

Colour: black matt

Place of assembly: Recessed mount in the wall

Width [mm]: 71 Height [mm]: 71

Diameter of an installation box: 60

Installation depth: 25 **Number of sockets**: 1

TECHNICAL DATA:

Rated voltage [V]: 250 AC Rated current [A]: 16

Class of protection against electric shock: |

Material of contacts: CuZn70

Earthing type: type F

Terminal type: Screw terminal

Plastic: ABS IP class: 44

LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 10

Number of units in the packaging: 120

Net unit weight [g]: 76 Grammage [g]: 89.75

Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 5 Height of a unit pack [cm]: 14

Weight of a cardboard box [kg]: 10.77 Width of a cardboard box [cm]: 26.5



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.







33613 LOGI 02-1230-142 cm

Socket Outlet Earthed - With Protection Cover - FireProof Plastic

Height of a cardboard box [cm]: 32 Length of a cardboard box [cm]: 44 Volume of a cardboard box [m³]: 0.037312

Date of issue: 15.11.2022, 21:13

ΕN