


33810 ONTEC S W1302MATWCLD

Emergency lighting LED 5902052529384













Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted Place of application: Indoors and outdoors

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Rated power [W]: 6,5 Rated power (LED) [W]: 2

Class of protection against electric shock: II

Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 204

Luminous flux [lm] (emergency-lighting module): 204

Colour temperature: cold white

Correlated colour temperature [K]: 5000

Ambient temperature range to which the product can be

exposed: -15÷40

Battery (type): LiFEPO4/C Battery (parameters): 6.4V

Operating mode: emergency and network **Application**: lighting of escape routes

Fail-safe working time [h]: 3

Automatic test: yes

Enclosure material: plastic

Connection type: Self-clamping block

IP class: 65

LOGISTIC DATA:


Unit of measurement: unit Packaging method: 20

Number of units in the secondary packaging: 1

Number of units in the packaging: 20

Net unit weight [g]: 576 Grammage [g]: 646

Gross unit weight [g]: 648







33810 ONTEC S W1302MATWCLD

Emergency lighting LED

Length of a unit pack [cm]: 27.5 Width of a unit pack [cm]: 4.5 Height of a unit pack [cm]: 15

Weight of a cardboard box [kg]: 12.92 Width of a cardboard box [cm]: 4.5 Height of a cardboard box [cm]: 15 Length of a cardboard box [cm]: 27.5 Volume of a cardboard box [m³]: 0.001856

ACCESSORIES

33829 OPRAWA DWUSTRONNA OS0



 33830
 UCHW PODT OS S2 S3 IT

 28985
 ZEST POD OR00 B

 33876
 ZEST MONT S20 FLAGA



 33871
 ZEST MONT OS05

 33877
 ZEST MONT OS205

 28974
 ZEST MON OS010 W

