

# **33823** ITECH C1 302 STW

**Emergency lighting LED** 

5902052530847





Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

### **GENERAL DATA:**

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors

Height [mm]: 66.5 Diameter [mm]: 170

Integrated LED light source: yes

#### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 2

Class of protection against electric shock: ||

**Diode type**: LED SMD **Luminous flux [lm]**: 238

Luminous flux [lm] (emergency-lighting module): 238

Colour temperature: cold white

Correlated colour temperature [K]: 5000

Ambient temperature range to which the product can be

exposed: 10÷40

**Battery (type)**: LiFEPO4/C **Battery (parameters)**: 6.4V

Operating mode: emergency and network Application: lighting of escape routes Fail-safe working time [h]: 3

an-sale working time

Standard test: yes

Enclosure material: plastic

Connection type: Self-clamping block


IP class: 65

## **LOGISTIC DATA:**

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1





# 33823 ITECH C1 302 STW

**Emergency lighting LED** 

**ACCESSORIES:** 

**33830** UCHW PODT OS S2 S3 IT

