


33827 ONTEC R C1 302 M STW

Emergency lighting LED

5902052529179



Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

GENERAL DATA:

Colour: white
Place of assembly: wall mounted, ceiling mounted
Place of application: Indoors
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Rated power (LED) [W]: 2
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 246
Luminous flux [lm] (emergency-lighting module): 246
Colour temperature: cold white
Correlated colour temperature [K]: 5000
Ambient temperature range to which the product can be exposed: 10÷35
Battery (type): LiFEPO4/C
Battery (parameters): 6.4V
Operating mode: emergency and network
Application: lighting of escape routes
Fail-safe working time [h]: 3
Standard test: yes
Enclosure material: plastic
Connection type: Self-clamping block
IP class: 20

LOGISTIC DATA:

Packaging method: 1
Number of units in the secondary packaging: 1
Number of units in the packaging: 1
Net unit weight [g]: 240
Length of a unit pack [cm]: 13.5
Width of a unit pack [cm]: 4
Height of a unit pack [cm]: 13.5
Width of a cardboard box [cm]: 15
Height of a cardboard box [cm]: 29
Length of a cardboard box [cm]: 21

Emergency lighting LED

Volume of a cardboard box [m³]: 0.009135

ACCESSORIES:

33831 ZEST PODT OR00 W

