

# **33833** ITECH S1 302MATW

**Emergency lighting LED** 

5902052541010





Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

### **GENERAL DATA:**

Colour: white Height [mm]: 66.5 Diameter [mm]: 170

Integrated LED light source: yes

## TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 2

Class of protection against electric shock: ||

**Diode type**: LED SMD **Luminous flux [lm]**: 245

Luminous flux [Im] (emergency-lighting module): 245

Colour temperature: cold white

Correlated colour temperature [K]: 5000

**Battery (type)**: LiFePO4/C **Battery (parameters)**: 6.4V

**Operating mode**: emergency and network

**Application**: anti-panic lighting **Fail-safe working time [h]**: 3

Automatic test: yes

Enclosure material: plastic

IP class: 65

## **LOGISTIC DATA:**

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

### **ACCESSORIES:**

**33830** UCHW PODT OS S2 S3 IT

