


## 33836 ITECH F2 105MATW

Emergency lighting LED

5902052531042



Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

### GENERAL DATA:

**Colour:** white

**Place of assembly:** wall mounted, ceiling mounted

**Place of application:** Indoors

**Height [mm]:** 66.5

**Diameter [mm]:** 170

**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 4.5

**Class of protection against electric shock:** II

**Diode type:** LED SMD

**Luminous flux [lm]:** 499

**Luminous flux [lm] (emergency-lighting module):** 499

**Colour temperature:** cold white

**Correlated colour temperature [K]:** 5000

**Ambient temperature range to which the product can be exposed:** 10÷40

**Battery (type):** LiFePO4/C

**Battery (parameters):** 6.4V

**Operating mode:** emergency and network

**Application:** lighting of escape routes

**Fail-safe working time [h]:** 1

**Automatic test:** yes

**Enclosure material:** plastic

**Connection type:** Self-clamping block

**IP class:** 65

### LOGISTIC DATA:

**Packaging method:** 1

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 1

Emergency lighting LED

### ACCESSORIES:

**33830** UCHW PODT OS S2 S3 IT