


#### ONTEC R M2 302 M ATW 33851

Emergency lighting LED

5902052529124













Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

#### **GENERAL DATA:**

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors Integrated LED light source: yes

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Rated power [W]: 7.2 Rated power (LED) [W]: 2

Class of protection against electric shock: ||

**Lampshade material**: plastic

Diode type: LED SMD Luminous flux [lm]: 288

Luminous flux [Im] (emergency-lighting module): 288

Colour temperature: cold white

Correlated colour temperature [K]: 5000

Ambient temperature range to which the product can be

exposed: 10÷35

Battery (type): LiFEPO4/C

Battery (parameters): 6,4V 1,5Ah

**Operating mode**: emergency and network

**Application**: anti-panic lighting Fail-safe working time [h]: 3

Automatic test: yes

**Enclosure material**: plastic

**Connection type**: Self-clamping block


IP class: 20

#### **LOGISTIC DATA:**

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1








# **33851** ONTEC R M2 302 M ATW

## **Emergency lighting LED**





We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

