


Emergency lighting LED 5902052520732





## 

Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

## GENERAL DATA:

Colour: white Place of assembly: wall mounted, ceiling mounted Integrated LED light source: yes

## TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Rated power (LED) [W]: 4.5 Class of protection against electric shock: II Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 615 Luminous flux [Im] (emergency-lighting module): 615 Colour temperature: cold white Correlated colour temperature [K]: 5000 Battery (type): LiFEPO4/C Battery (parameters): 6.4V **Operating mode**: emergency and network **Application**: anti-panic lighting Fail-safe working time [h]: 1 Standard test: yes **Enclosure material**: plastic **Connection type**: Self-clamping block **IP class**: 20

## LOGISTIC DATA:

Packaging method: 1 Number of units in the secondary packaging: 1 Number of units in the packaging: 1 Net unit weight [g]: 238 Grammage [g]: 282 Length of a unit pack [cm]: 13.5 Width of a unit pack [cm]: 13.5 Width of a unit pack [cm]: 13.5 Weight of a cardboard box [kg]: 0.282 Width of a cardboard box [kg]: 0.282 Width of a cardboard box [cm]: 4 Height of a cardboard box [cm]: 13.5 Length of a cardboard box [cm]: 13.5 Volume of a cardboard box [m<sup>3</sup>]: 0.000729





Emergency lighting LED



