

# iQ-LED

## Kanlux

### 33884 IQ-LED FL-90W-NW

LED floodlight

5905339338846



up to  
**120** lm  
/ W

DESIGN  
unique

LED  
technology



Kanlux IQ FL floodlights are unique products. Their automatic production allows ensuring the highest quality and repeatability of lighting parameters. They include brand LEDs with a life span of 50,000 hours, which is also their additional advantage. The use of the highest quality components allows us to provide our customers with a five-year warranty for the whole series of Kanlux IQ FL floodlights.

#### GENERAL DATA:

**Colour:** black  
**Place of assembly:** wall mounted, ceiling mounted  
**Place of application:** outdoors  
**Minimum distance from the illuminated object:** 1m  
**Compatible with a dimmer:** no  
**RAL:** 7024  
**Wykrywanie ruchu:** no  
**Width [mm]:** 243  
**Height [mm]:** 314  
**Depth [mm]:** 38  
**Mercury content:** no  
**Integrated LED light source:** yes

#### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 90  
**Class of protection against electric shock:** I  
**Lampshade material:** Tempered glass  
**Diode type:** LED SMD  
**Luminous flux [lm]:** 10800  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 12000  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)  
**Colour temperature:** white  
**Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:**  $\leq 6$   
**Colour rendering index:** 80

Date of issue: 31.01.2024, 10:43

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.


EN

# iQ-LED

## Kanlux

### 33884 IQ-LED FL-90W-NW

LED floodlight



**Service life [h]:** 50000

**Number of on/off cycles:**  $\geq 25000$

**Lighting angle [°]:** 100

**Luminous efficiency of the lamp [lm/W]:** 120

**Ambient temperature range to which the product can be exposed:** -30÷50

**Enclosure material:** Metal

**Connection type:** Free cable ends

**Wire type:** H05RN-F

**Wire length [m]:** 0.3

**Wire diameter [mm<sup>2</sup>]:** 1

**Lamp-heating time [s]:**  $\leq 1$

**Lamp-ignition time [s]:**  $\leq 0,5$

**The fixture is movable vertically [°]:** 180

**IP class:** 65

#### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 5

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 5

**Net unit weight [g]:** 1264

**Grammage [g]:** 1450

**Gross unit weight [g]:** 1332

**Length of a unit pack [cm]:** 24.5

**Width of a unit pack [cm]:** 4

**Height of a unit pack [cm]:** 32

**Weight of a cardboard box [kg]:** 7.25

**Width of a cardboard box [cm]:** 24

**Height of a cardboard box [cm]:** 37

**Length of a cardboard box [cm]:** 30

**Volume of a cardboard box [m<sup>3</sup>]:** 0.02664

#### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website
- 

Date of issue: 31.01.2024, 10:43


We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

EN


**33884 IQ-LED FL-90W-NW**

LED floodlight



KANLUX S.A. (kat 33884) IQ-LED FL-90W-NW / LDC (Polar)

Luminaire: KANLUX S.A. (kat 33884) IQ-LED FL-90W-NW  
Lamps: 1 x IQ-LED FL-90W-NW



**ACCESSORIES**

**33889**

**IQ-LED FL QC I 3x1MM2**



Hermetic quick connector for easy, quick and safe connection of the connecting cable and the floodlight, IQ-LED FL QC I 3x1MM2 (33889)