

33893 MEBA LED 40W IP54 NW

Linear LED luminaire 5905339338938


























Kanlux MEBA LED IP54 is a series of surface-mounted luminaires that complements the popular family of Kanlux MEBA luminaires. We can choose from models with a length of 600mm and 1200mm. Kanlux MEBA LED IP54 means high luminous efficiency, durability of 50,000 hours and a 5-year warranty. An additional advantage of these luminaires is the IP54 level and two cable entries that allow for pass-through connection. The quick connector makes it easier to install the luminaire, and the lampshade and sides of the luminaire are made of polycarbonate and the body is made of steel sheet. These are other advantages of these luminaires.

GENERAL DATA:

Colour: white

Place of assembly: ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Length [mm]: 1213 Width [mm]: 152 Height [mm]: 57

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 40

Class of protection against electric shock: I

Lampshade material: PC Diode type: LED SMD Luminous flux [lm]: 5200

Useful luminous flux of the light source Φ use [lm]: 2x 3380 Useful luminous flux of the light source Φ use [lm]: in sphere

(360°)

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: 6

Colour rendering index: 80 Service life [h]: 50000

Number of on/off cycles: ≥25000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 130

Ambient temperature range to which the product can be

exposed: -20+40

Date of issue: 05.01.2024, 11:50

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





MEBA LED 40W IP54 NW 33893

Linear LED luminaire



Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,75-2

IP class: 54

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 6

Number of units in the secondary packaging: 1

Number of units in the packaging: 6

Net unit weight [g]: 1446 Grammage [g]: 1758.33

Length of a unit pack [cm]: 122 Width of a unit pack [cm]: 15.5 Height of a unit pack [cm]: 6.5

Weight of a cardboard box [kg]: 10.54998

Width of a cardboard box [cm]: 20 Height of a cardboard box [cm]: 33 Length of a cardboard box [cm]: 125 Volume of a cardboard box [m³]: 0.0825

ADDITIONAL INFORMATION:

• 5 years Warranty under the terms of the warranty statement, available on our website

