

## **33960** AL-SL-NW-MAT-S-PT


Linear LED luminaire

5905339339607











#### **GENERAL DATA:**

Colour: silver

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no Fixture lighting direction: down

Length [mm]: 590 Width [mm]: 83 Height [mm]: 65

Integrated LED light source: yes

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 10

Class of protection against electric shock: I

Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 1300 Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤3

Colour rendering index: 80 Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :

L90B10

Number of on/off cycles: ≥30000 Lighting angle [°]: X85/Y95

Luminous efficiency of the lamp [lm/W]: 130

Ambient temperature range to which the product can be

**exposed**: 5÷25 **Shade type**: matt

Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm²]:  $1,5 \div 2,5$ 


Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IP class: 20

### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Date of issue: 02.03.2023, 02:41





Photometry: the results obtained from testing were from a specific sample.



# **33960** AL-SL-NW-MAT-S-PT

### Linear LED luminaire

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 932 Grammage [g]: 1110

Length of a unit pack [cm]: 75 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 1.11
Width of a cardboard box [cm]: 11
Height of a cardboard box [cm]: 7
Length of a cardboard box [cm]: 75

Volume of a cardboard box [m³]: 0.005775

### **ADDITIONAL INFORMATION:**

• 5 years Warranty under the terms of the warranty statement, available on our website

KANLUX S.A. (kat 33960) AL-SL-NW-MAT-S-PT / LDC (Polar)



