


## 34130 AL-LL-WW-MAT-B-PT

Linear LED luminaire 5905339341303









# CE ERE LATA:

Colour: black Place of assembly: Recessed mount in the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Compatible with a dimmer: no Fixture lighting direction: down Length [mm]: 1710 Width [mm]: 83 Height [mm]: 65 Integrated LED light source: yes

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 33 Class of protection against electric shock : | Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 4100 Colour temperature: Warm white Correlated colour temperature [K]: 3000 Colour consistency in McAdam ellipses : ≤3 Colour rendering index: 80 Service life [h]: 50000 Luminous-flux-retention factor at the end of rated service life : L90B10 Number of on/off cycles: ≥30000 Lighting angle [°]: X85/Y95 Luminous efficiency of the lamp [lm/W]: 124 Ambient temperature range to which the product can be exposed: 5+25 Shade type: matt Enclosure material: steel Connection type: Self-clamping block Range of sections of wires used [mm<sup>2</sup>]: 1,5÷2,5 Lamp-heating time [s]: ≤1 Lamp-ignition time [s]: ≤0,5 IP class: 20

#### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Date of issue: 02.03.2023, 00:15

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.



## 34130 AL-LL-WW-MAT-B-PT

Linear LED luminaire

Number of units in the secondary packaging: 1 Number of units in the packaging: 1 Net unit weight [g]: 2290 Grammage [g]: 2730 Length of a unit pack [cm]: 182 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7 Weight of a cardboard box [kg]: 2.73 Width of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 7 Length of a cardboard box [cm] : 182 Volume of a cardboard box [m<sup>3</sup>]: 0.014014

#### ADDITIONAL INFORMATION:

• 5 years Warranty under the terms of the warranty statement, available on our website

