

# 34189 ALD-SH-NW-MAT-W-PT


Linear LED luminaire 5905339341891













### **GENERAL DATA:**

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: DALI Fixture lighting direction: down

Length [mm]: 590 Width [mm]: 83 Height [mm]: 65

Integrated LED light source: yes

### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 19

Class of protection against electric shock:

Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 2550 Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤3

Colour rendering index: 80 Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :

L90B10

Number of on/off cycles: ≥30000 Lighting angle [°]: X85/Y95

Luminous efficiency of the lamp [lm/W]: 134

Ambient temperature range to which the product can be

exposed: 5÷25 Shade type: matt

Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm<sup>2</sup>]: 0,5÷2,5

Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IP class: 20

#### LOGISTIC DATA:

**Unit of measurement**: unit **Packaging method**: 1

Date of issue: 03.03.2023, 03:16

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





# 34189 ALD-SH-NW-MAT-W-PT

#### Linear LED luminaire

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1023 Grammage [g]: 1215

Length of a unit pack [cm]: 74.5 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 1.215
Width of a cardboard box [cm]: 11
Height of a cardboard box [cm]: 7
Length of a cardboard box [cm]: 74.5
Volume of a cardboard box [m³]: 0.005737

#### **ADDITIONAL INFORMATION:**

• 5 years Warranty under the terms of the warranty statement, available on our website

