



Linear LED luminaire

5905339343369



**DALI**  
system



### GENERAL DATA:

**Colour:** white  
**Place of assembly:** ceiling mounted  
**Place of application:** Indoors  
**Minimum distance from the illuminated object:** 0,5m  
**Compatible with a dimmer:** DALI  
**Fixture lighting direction:** down  
**Length [mm]:** 1700  
**Width [mm]:** 60  
**Height [mm]:** 69  
**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 33  
**Class of protection against electric shock:** I  
**Lampshade material:** plastic  
**Diode type:** LED SMD  
**Luminous flux [lm]:** 4150  
**Colour temperature:** white  
**Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:** ≤3  
**Colour rendering index:** 80  
**Service life [h]:** 50000  
**Luminous-flux-retention factor at the end of rated service life:** L90B10  
**Number of on/off cycles:** ≥30000  
**Lighting angle [°]:** X75/Y90  
**Luminous efficiency of the lamp [lm/W]:** 126  
**Ambient temperature range to which the product can be exposed:** 5÷25  
**Shade type:** microprismatic  
**Enclosure material:** aluminum alloy  
**Connection type:** Self-clamping block  
**Range of sections of wires used [mm²]:** 0,5÷2,5  
**Lamp-heating time [s]:** ≤1  
**Lamp-ignition time [s]:** ≤0,5  
**IP class:** 20

### LOGISTIC DATA:

**Unit of measurement:** unit  
**Packaging method:** 1

### Linear LED luminaire



**Number of units in the secondary packaging :** 1

**Number of units in the packaging :** 1

**Net unit weight [g] :** 2955

**Grammage [g] :** 3405

**Length of a unit pack [cm] :** 182

**Width of a unit pack [cm] :** 11

**Height of a unit pack [cm] :** 7

**Weight of a cardboard box [kg] :** 3.405

**Width of a cardboard box [cm] :** 11

**Height of a cardboard box [cm] :** 7

**Length of a cardboard box [cm] :** 182

**Volume of a cardboard box [m<sup>3</sup>] :** 0.014014

#### **ADDITIONAL INFORMATION:**

- 5 years Warranty under the terms of the warranty statement, available on our website

### ACCESSORIES

32543



ALIN CORD DALI 1F-W

Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, white, 150 cm

32544



ALIN CORD DALI 1F-B

Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, black, 150 cm

32545



ALIN CORD DALI 1F-SR

Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, silver, 150 cm

07871



ROPE-NT 150 SINGLE

ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set

29557



ALIN NT GRIP

Wall bracket for the ALIN luminaire, 2 pcs included