

34360 ALD-LL-NW-MPR-S-NT


Linear LED luminaire 5905339343604











UK CA EAE CE **GENERAL DATA:**

Colour: silver Place of assembly: ceiling mounted Place of application: Indoors Minimum distance from the illuminated object: 0,5m Compatible with a dimmer: DALI Fixture lighting direction: down Length [mm]: 1700 Width [mm]: 60 Height [mm]: 69 Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 33 Class of protection against electric shock : | Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 4150 Colour temperature: white Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses : ≤ 3 Colour rendering index: 80 Service life [h]: 50000 Luminous-flux-retention factor at the end of rated service life : L90B10 Number of on/off cycles: ≥30000 Lighting angle [°]: X75/Y90 Luminous efficiency of the lamp [lm/W]: 126 Ambient temperature range to which the product can be exposed: 5+25 Shade type: microprismatic Enclosure material: aluminum alloy Connection type: Self-clamping block Range of sections of wires used [mm²]: 0,5÷2,5 Lamp-heating time [s]: ≤1 Lamp-ignition time [s]: ≤0,5 IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Date of issue: 01.03.2023, 19:44

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.



34360 ALD-LL-NW-MPR-S-NT

Linear LED luminaire



Number of units in the secondary packaging: 1 Number of units in the packaging: 1 Net unit weight [g]: 2955 Grammage [g]: 3405 Length of a unit pack [cm]: 182 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7 Weight of a cardboard box [kg]: 3.405 Width of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 11 Height of a cardboard box [cm]: 7 Length of a cardboard box [cm] : 182 Volume of a cardboard box [m³]: 0.014014

ADDITIONAL INFORMATION:

• 5 years Warranty under the terms of the warranty statement, available on our website



34360 ALD-LL-NW-MPR-S-NT

Linear LED luminaire

ACCESSORIES		
32543	ALIN CORD DALI 1F-W	Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, white, 150 cm
32544	ALIN CORD DALI 1F-B	Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, black, 150 cm
32545	ALIN CORD DALI 1F-SR	Power supply terminal for ALIN luminaires and tracks, 1-phase, DALI, silver, 150 cm
07871	ROPE-NT 150 SINGLE	ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set
29557	ALIN NT GRIP	Wall bracket for the ALIN luminaire, 2 pcs included

